Supplier - DOVER

Mayco Base 4212

Dark Color Sulfurized Additives

Sulfurized Methyl Ester

## **Typical Properties**

Appearance	Dark Brown Fluid
Specific Gravity@15.6℃	0.980
Density,lb/gal	8.17
Viscosity@40°C,cSt	70
Viscosity@100°F,SUS	325
Sulfur Content(Active),%wt	17 (7)
Neutralization Number,meqKOH/g	4
Flash Point C.O.C.,°F( °C)	> 350 (> 177)
Copper Corrosion+	4b
Std Packaging (NW / GW, Kg)	217.0 / 200.0

## **Product Description**

**MAYCO BASE 4212** is a sulphurized methyl ester designed to be used in products where low viscosity, excellent base oil (especially highly refined paraffinic), stability, and high wetting characteristics are some of the more important features of the finished cutting oil.

**MAYCO BASE 4212** can be utilized as a performance booster sump-side, as it will readily mix with the currently used product in the system, if applied at a point of even mild agitation or circulation.

MAYCO BASE 4212 may find use in products designed for gun drilling, honing, and heavy duty grinding.

**MAYCO BASE 4212** contains active sulfur; it should not be used in products destined for applications on the yellow metals (copper, brass, and bronzes).

<u>Applications</u>	Suggested Treat Rates, %wt
Straight Oil Machining	2 - 15
Straight Oil Machining	2 - 15
Drawing / Stamping	3 - 10
Soluble Oil Machining	5 - 15

Print date: 28-04-24