Supplier - SMART OIL
Smart Base 1410

0

Sulfurized Fatty Oil

## **Typical Properties**

Appearance	Brown Liquid
Specific Gravity@25℃	0.950 - 1.000
Viscosity@40°C, cSt	100 - 200
Sulfur Content (Active), %wt	9 - 11 (0)
Acid Value, mgKOH/g	≤ 8
Flash Point C.O.C., °C	> 160
Copper Corrosion+	1B
$P_B/P_D$ , kg++	82 / 200
Std Packaging (NW / GW, Kg)	200.0 / 217.0

## **Product Description**

**SMART BASE 1410** is a non-active sulfurized fatty oil, suitable for machining non-ferrous and ferrous metals.

**SMART BASE 1410** gives a clear dark red amber translucent fluid when blended with base oil at 5%; with low viscosity, so easy to blend.

**SMART BASE 1410** possesses superior lubricity and EP properties; it can improve surface finishing of workpieces after operation.

**SMART BASE 1410** possesses excellent compatibility. It can be used with majority of mineral oils, and can be used in extensive formulations like cutting oils, drawing oils and cold heading oils.

<u>Applications</u>	<u>Suggested Treat Rates, %wt</u>
Gear Cutting	5 - 10
Cold Heading	25 - 50
Automatic Screw Machine	10 - 20

Print date: 11-07-25