Supplier - SMART OIL
Smart Base 3517
Light Color Sulfurized Additives

Sulfurized Fatty Oil

## **Typical Properties**

Appearance	Amber Liquid
Specific Gravity@25°C	0.900 - 1.000
Viscosity@40°C, cSt	200 - 400
Sulfur Content (Active), %wt.	15 - 17
Acid Value, mgKOH/g	< 8
Flash Point C.O.C.,°C	> 150
Copper Corrosion+	4B
$P_B/P_D$ kg, kg++	88 / 315
Std Packaging (NW / GW, Kg)	217.0 / 200.0

## **Product Description**

**SMART BASE 3517** is a kind of amber, high viscosity, low-odor fatty oil; with excellent lubricating and extreme pressure properties, it is recommended for use in neat oil formulations for the processing ferrous metals.

**SMART BASE 3517** is suitable for heavy-duty processing like tapping, drawing, stamping and turning. Compared with other additives similar sulfur content, **SMART BASE 3517** exhibits better lubrication and EP performance, that can effectively enhance the surface finishing of workpieces and extend the tool life.

**SMART BASE 3517** has good compatibility in different groups of base oils that make it easy to blend different types of processing oil.

**SMART BASE 3517** contains active sulfur, which is not suitable for the processing ordinary copper, bronze, and brass.

Applications	Suggested Treat Rates, %wt
Threading	8 - 15
Tapping	10 - 20
Cold Head (Cut Side Only)	8-15
Automatic Screw Machines (Cut Side	5 - 12
Only)	

Print date: 14-05-24