Supplier - SMART OIL
SmartFort LB6210

Lubricity / Anti-wear Booster High Molecular Fatty Acid Ester Package

Typical Properties

Appearance
Specific Gravity@25°C
pH Value (5% Water Dilution)
Viscosity@40°C, cSt
Acid Value, mgKOH/g
Std Packaging (NW / GW, Kg)

Light Amber Liquid 0.950 - 1.050 7.0 - 8.5 250 - 450 < 110 212.0 / 195.0

Product Description

SMARTFORT LB6210 is a water-based lubricity and EP booster, with wetting and surface finishing properties.

SMARTFORT LB6210 contains no sulfur, chlorine, phosphorous, nitrite or other harmful materials, which is designed to use in used in fully-synthetic,semi-synthetic and soluble oil formulations

SMARTFORT LB6210 exhibits synergistic effect when it is used together with other water-based extreme pressure additives such as **SMARTSUL W4772** or **SMARTPHOS W5880**, which can significantly boost the EP performance.

SMARTFORT LB6210 can be diluted with water for application of stamping and drawing fluids for copper and aluminum alloys.

SMARTFORT LB6210 can be used as tank side additive to improve fluid performance, which can specially boost the surface finishing of workpieces.

ApplicationsGeneral Machining

Suggested Treat Rates, %wt

Print date: 30-04-24