Supplier - SMART OIL
Smart Base WLA6600

Light Color Waylube Additives Waylube Additive Package

## **Typical Properties**

Appearance	Light Brown Liquid
Specific Gravity@25°C	0.900 - 1.000
Viscosity@40°C, cSt	30 - 50
Acid Value, mgKOH/g	< 60
Flash Point C.O.C., °C	> 135
Copper Corrosion+	1B
$P_B/P_D$ , kg++	61 / 200
Std Packaging (NW / GW, Kg)	197.0 / 180.0

## **Product Description**

**SMART BASE WLA6600** contains phosphorus, fatty acid, antioxidant and demulsifying agent; but no sulfur, chlorine and ZDDP. It exhibits excellent anti-wear, antioxidant, non-corrosive and oil-water separation properties.

**SMART BASE WLA6600** can ensure the sideways to have a thin and uniform oil film, so that the table motion can be in an ultra-smooth condition. It can eliminate the "stick-slip" tendency of heavily loaded table when it is sliding at slow speeds or upon machine start-up; even after long periods of machine shutdown.

**SMART BASE WLA6600** is fortified with rust and oxidation inhibitors, which make it suitable for blending hydraulic and gear oils.

**SMART BASE WLA6600** can be blended with tackifier such as **SmartTac H** and Group I ISO 68 base oil to prepare way lubricant of the **CINCINNATI MILACRON P-47** type.

Way Lube Formulation	
<u>Items</u>	Treat Rates, %wt
Group I/II Base Oil	98
Smart Base WLA6600	1.5
SmartTac H (tackifier )	0.5

Print date: 08-05-24