

Supplier -

*Polyol Esters  
TMP Complex Esters*

### Typical Properties

Appearance@25°C	Light-colored Liquid
Color,ASTM D1544,Gardner/D1500	≤ 8/2.5
Viscosity@40°C,cSt	50 - 70
Total Acid Value,mgKOH/g	≤ 8.0
Pour Point,°C(°F)	≤ 6 (42)
Moisture Content,%wt	≤ 0.1
Flash Point C.O.C.,°C(°F)	≥ 200 (392)
Fire Point C.O.C.,°C(°F)	≥ 275 (527)
Saponification Number,mgKOH/g	185 - 210

### Product Description

**Adtec™ 426** is high quality complex esters of trimethylolpropane (TMP) that offers excellent lubrication characteristics comparable to trimethylolpropane trioleate (TMPTO), but at a significantly lower cost. It exhibits excellent high temperature stability shown to have fire resistant properties, and also has favorable clean burning-off properties that minimize surface residue in hot rolling applications. **Adtec™ 426** is designed with high TAN to be used in applications requiring high acidity. It proves to be biodegradable according to the European 21 days and EPA 28 days biodegradability tests.

#### Applications:

**Adtec™ 426** has found application in the metalworking industry for use in steel milling, grinding, cutting oils, hot or cold rolling oils and drawing lubricants. With its high thermal stability and biodegradability, it can be a cheaper alternative as a base stock for hydraulic fluids for outdoor mobile equipment.

Print date: 08-05-24

**Disclaimer:** Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.