

Supplier - FUNCTIONAL

PD-600

0

*Cold-flow Improver for Mineral Oil-based Lubricants***Typical Properties**

Appearance	Light-colored Liquid
Odor	Mild Fatty
Specific Gravity	0.880
Density, lbs/gal	7.33
Flash Point, °C(°F)	≥ 135 (275)
Kinematic Viscosity@100°C,cSt	70
Std Packaging (NW / GW, Kg)	200.0 / 217.0

Product Description

FUNCTIONAL PD-600 is a wax-crystal modifier. Its primary use is in improving the cold-flow properties of mineral oil-based lubricants at temperatures below their cloud points. It is effective under both rapid cooling and extended cold storage conditions.

FUNCTIONAL PD-600 is effective in hydraulic fluids, chain saw oils, pneumatic-tool lubricants and other lubricants made from solvent extracted neutral base stocks as well as hydro-cracked base stocks.

Composition:

The active additive in **FUNCTIONAL PD-600** is a proprietary polymer. The diluent oil in **FUNCTIONAL PD-600** is light paraffinic oil.

Handling:

Any convenient technique may be used for blending. Safe handling precautions are the same as those to be taken with vegetable oils; see the current Material Safety Data Sheet.

Applications**Suggested Treat Rates, %wt**

Reduce Pour Point of Mineral Oils (□ 40°F)	0.1
Stability in Extended Storage (□ 40°F)	0.2

Print date: 16-07-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.