Supplier - SMART OIL
Smart DPE1506

Polyol Ester

High viscosity index, good shear stability, with good affinity to meta

## **Typical Properties**

Appearance Clear Amber Liquid Specific Gravity@25°C 0.900 - 1.000 Viscosity@40°C, cSt 110 - 150 Acid Value, mgKOH/g < 15 Flash Point C.O.C.,°C > 240 Viscosity Index > 160 Mineral Oil Content Nil Std Packaging (NW / GW, Kg) 212.0 / 195.0

## **Product Description**

**SMART PE1506** is a clear amber dipentaerythritol compound ester, which possesses unique structure that contributes a strong affinity property to the metal surface; which results to maintain superior lubricating properties and anti-frictional characteristics even under high temperature during processing.

**SMART PE1506** is designed for the blenders to manufacture water or oil-based cutting fluid for steel rolling, aluminum or copper drawing fluid applications.

SMART PE1506 has a high degree of saturation that can prevent contamination from oxidation.

**SMART PE1506** can effectively replace the sulfur, chlorine and phosphorous containing compounds as EP additives. In addition, it can avoid the adverse effect on product shininess due to the otherwise chemical reaction of the extreme additives with the metal during machining.

**SMART PE1506** has high viscosity index and good shear stability, which can maintain lubrication, wear resistance and extreme pressure performance at the contact points between the tool and the workpiece at high temperature.

**SMART PE1506** is an ashless additive and has no residue during high temperature operation. It has no corrosion to non-ferrous metals and is suitable for cutting, drawing, and stamping operation for aluminum alloy.

**SMART PE1506** has good compatibility with mineral oil, synthetic oil and synthetic ester with easy blending.

**SMART PE1506** is a biodegradable product that can replace mineral oil as a lubricant on top of its multifunctional characteristics in cutting fluid.

Print date: 02-05-24