Supplier - ARKEMA SPS 10LS 0 Extreme Pressure Lubricant Additive

Typical Properties

Density@20°C,kg/m³	1250
Viscosity@20°C,mPa.s	< 100
Melting point,°C	< 4
Boiling point,°C	> 100
Flash Point,°C,(Close Cup)	> 110
Std Packaging (NW / GW, Kg)	250.0 / 267.0

Product Description

SPS 10LS is a water soluble sulfur additive (10%sulfur) showing excellent extreme pressure properties and designed for water miscible fluids.

SPS 10LS is compatible with synthetic and semi-synthetic fluids.

Key properties

readily biodegradable, colorless and odorless, limpid, free of unsatured hydrocarbon residues, non-foaming and fully water-miscible.

Stable, transparent and non foaming,

SPS 10LS is the ideal way to boost exterme pressure performances of synthetic or semi-synthetic metalworking fluids formulations.

Print date: 12-07-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressively requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents belong to the respective companies, or from their sources.