

Supplier - FUNCTIONAL

V-255

Shear Stable Polymer

Viscosity Modifiers

Typical Properties

Appearance	White Rubber
Specific Gravity	0.870
Shear Stability Index,ASTM D-6278,%	25

Product Description

Shear stable polymer in pellet form.

Applications

General Treat Level, %wt
Application Recommendation
Viscosity Treat Rate (ISO32), @100°C
Treat To Obtain□1000 cSt, @100°C), %

Suggested Treat Rates, %wt

0.5 - 2.0
Lubrication Greases, Lub Oils, Gear Oils, Engine Oils
1 % = 10.5 cSt
12

Print date: 22-09-26

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.