Supplier - DOVER

Mayco Base 1351

Sulfurized Fatty Oil

Dark Color Sulfurized Additives

Typical Properties

Appearance	Dark Brown Fluid.
Specific Gravity@60/60°F	0.970
Density,lb/gal	8.07
Viscosity@100°F(210°F),SUS	1775 (175)
Viscosity@100°F(210°F),cSt	375 (35)
Total Sulfur(Active),%wt	10.5 (0)
Neutralization,meqKOH/g	≤ 8
Flash Point C.O.C.,°F(°C)	> 400 (> 204)
Copper Corrosion+	1b

^{+10%} additive in SN150, 3h, 100

Product Description

MAYCO BASE 1351 is a sulfurized fatty material, which due to its low viscosity lends itself to a variety of ferrous application needs.

MAYCO BASE 1351 can also be used in severe operations on difficult to machine brass and bronzes due to its non-staining characteristic.

MAYCO BASE 1351 can be used in dual-purpose applications and is an additive of choice in the formulation of way lubricants, where the recommended treat is 5% by weight.

Applications	Suggested Treat Rates, %wt
Waylube	5
Tapping	10 - 15
Cold Fordging	25 - 50
Tapping / Automatic Screw Machines	10 - 20
Turning	5 - 10

Print date: 04-12-25