Supplier - DOVER

Base 10SE

Sulfurized Methyl Ester

Dark Color Sulfurized Additives

## **Typical Properties**

Appearance	Dark Brown Fluid
Specific Gravity@25°C	0.940
Density,lb/gal	7.8
Viscosity@40°C(100°C),cSt	19 (4)
Viscosity@100°F(210°F),SUS	100 (40)
Total Sulfur (Active),%wt	10 (<0.5)
Acid Value,mgKOH/g	5
Flash Point, C.O.C.,°F(°C)	> 350 (> 177)
Pour Point,°F(°C)	60 (16)
Copper Corrosion+	1b

<sup>+10%</sup> additive in SN150, 3h, 100

## **Product Description**

**BASE 10SE** is a 10% sulfurized methyl ester designed to offer both lubricity and extreme pressure properties in oil and water dilutable metalworking fluids.

**BASE 10SE** is suitable for products destined for use in yellow metal applications (will not stain).

**BASE 10SE** can be utilized in straight oil machining, drawing and stamping, as well as a soluble oil component.

<u>Applications</u>	Suggested Treat Rates, %wt
Straight Oil Machining	5 - 15
Straight Oil Drawing & Stamping	3 - 10
Soluble Oil Machining	2 - 10

Print date: 07-11-25