Supplier - SMART OIL Smart Base 1217 Sulfurized Fatty Oil

Dark Color Sulfurized Additives

Typical Properties

Appearance	Dark Brown Liquid
Specific Gravity@25℃	1.000 - 1.100
Viscosity@40°C, cSt	700 - 1100
Sulfur Content (Active), %wt	16 - 19 (6)
Acid Value, mgKOH/g	≤ 8
Flash Point C.O.C., °C	> 190
Copper Corrosion+	4B
P_B/P_D , $kg++$	94 / 315

^{*10%} additive in SN150, 3h, 100

Product Description

SMART BASE 1217 is a sulfurized lard oil additive; suitable for machining various kinds of ferrous metals.

SMART BASE 1217 designed for using in formulations of neat oil operation on difficult-to-machine ferrous metals.

SMART BASE 1217 contains active sulfur, which is not recommended for the machining of copper, brass, or bronze alloys.

<u>Applications</u>	Suggested Treat Rates, %wt
Threading	10 - 20
Threading	10 - 20
Cold Heading (Cut Side Only)	20 - 30
Threading	10 - 20
Turning	5 - 10

Print date: 15-12-25

^{**4} Ball Wear Test; 5% additive in SN150, Servo Motor Speeds reach 1500rpm (PB) and 1760rpm (PD) in 0.03sec.