Supplier - SMART OIL Smart Base 1219

Sulfurized Fatty Oil
Dark Color Sulfurized Additives

Typical Properties

Appearance Dark Brown Liquid Specific Gravity@25°C 1.000 - 1.100 Viscosity@40°C, cSt 550 - 850 Sulfur Content (Active), %wt 17 - 20 (6) Acid Value, mgKOH/g ≤ 8 Flash Point C.O.C., °C > 190 Copper Corrosion+ 4B P_B / P_D , kg++ 88 / 315

Product Description

SMART BASE 1219 is a sulfurized fatty oil additive with relatively high sulfur content. It possesses high lubricity, can exhibit superior performance in cold heading and drawing oil formulations.

SMART BASE 1219 possesses superior EP properties, so it is specially suitable for machining tough metals like stainless steels and titanium alloys.

SMART BASE 1219 contains active sulfur; so it is not suitable for processing copper, bronze and brass.

<u>Applications</u>	Suggested Treat Rates, %wt
Reaming	10 - 20
Reaming	10 - 20
Cold Heading (Cut Side Only)	20 - 30
Reaming	10 - 20
Turning	5 - 10

Print date: 15-12-25

⁺10% additive in SN150, 3h, 100

^{**4} Ball Wear Test; 5% additive in SN150, Server Motor Speeds reach 1500rpm (P_B) and 1760rpm (P_D) in 0.03sec.