Supplier - SMART OIL
Smart Base 2617

0

Sulfurized Fatty Oil

Typical Properties

Appearance	Deep Amber To Dark Liquid
Specific Gravity@25℃	0.900 - 1.000
Viscosity@40°C, cSt	50 - 80
Sulfur Content (Active), %wt	14 - 18
Acid Value, mgKOH/g	≤ 4
Flash Point C.O.C., °C	> 170
Copper Corrosion+	4B
P_B / P_D , kg++	88 / 315
Std Packaging (NW / GW, Kg)	200.0 / 217.0

Product Description

SMART BASE 2617 is a highly cost-effective, sulfurized fat oil with a dark amber to brown appearance; but turns to light amber after it is blended with mineral oil.

SMART BASE 2617 contains active sulfur, which is not recommended for the machining of copper, brass, or bronze alloys.

SMART BASE 2617 possesses low viscosity, so is specially suitable for formulating deep drilling and honing oils; which require extremely superior cleansing property.

SMART BASE 2617 possesses excellent lubricating, anti-wear and EP properties. It exhibits more superior performance when blended with phosphate esters such as **SMARTPHOS P6800** / **P7800** and chlorine replacement additive like **SMART BASE CR-2050**.

SMART BASE 2617 is light color, so operations can easily be monitored. Its low odor can be accepted easily by workers.

SMART BASE 2617 has good stability and compatibility with other additives and different groups of base oils, which make it easy for blenders to use for blending different types of machining oils.

Applicati	ons	Suggested Treat Rates, %wt
Threadin	ng	3 - 15
Tapping		3 - 15
Cold Hea	ading (Cut Side Only)	5 - 20
Automat	ic Screw Machines (Cut Side	5 - 10
Only)		
Turning		2 - 8
Tapping Cold Hea Automat Only)	ading (Cut Side Only)	3 - 15 5 - 20 5 - 10

Print date: 13-07-25