Supplier - SMART OIL
Smart Base 2916
Sulfurized Fatty Oil
Light Color Sulfurized Additives

Typical Properties

Appearance	Amber Liquid
Specific Gravity@25℃	0.900 - 1.100
Viscosity@40°C, cSt	170 - 250
Sulfur Content, %wt	14 - 16
Acid Value, mgKOH/g	≤ 2
Flash Point C.O.C., °C	> 150
Copper Corrosion+	4B
P_B / P_D , kg++	82 / 315

Product Description

Applications

SMART BASE 2916 is a kind of amber, high viscosity, low-odor fatty oil; with excellent lubricating and extreme pressure properties, it is recommended for use in neat oil formulations for the processing ferrous metals.

SMART BASE 2916 is suitable for tapping, drawing, stamping, turning and other heavy-duty processing. Compared with other additives with similar sulfur content, **SMART BASE 2916** exhibits better EP and lubrication performance that can effectively elevate the surface finishing, and can extend tool life.

SMART BASE 2916 exhibits good compatibility in different groups of base oil that make it easy to blend different types of processing oil.

SMART BASE 2916 contains active sulfur, which is not suitable for processing ordinary copper, bronze, and brass.

Suggested Treat Bates 0/ wt

<u>Applications</u>	<u>Suggested freat Kates, %wt</u>
Threading	8 - 15
Tapping	8 - 20
Cold Heading (Cut Side Only)	8 - 15
Automatic Screw Machines (Cut Side	5 - 12
Only)	

Print date: 29-11-25