Supplier - DOVER

Doverlube NCL-2

Phosphate Anti-wear EP Additive

Typical Properties

Appearance	Transparent dark brown fluid
Specific Gravity@50°C	0.980
Viscosity@100°F(210°F),SUS	10000 (540)
Odor	Mild,fatty
Phosphorus Content,%wt	3.0
Acid Number,mgKOH/g	150
Flash Point C.O.C.,°F	450
Color, Gardner	11+
Std Packaging (NW / GW, Kg)	198.0 / 181.0

Product Description

DOVERLUBE NCL-2 is a proprietary, non-chlorinated lubrication additive containing non-halogenated extreme Pressure (EP)and anti-wear additives.

DOVERLUBE NCL-2 is based on phosphorous chemistry and a novel chemical principle; unlike other nonchlorinated additives, it does not rely on viscosity to perform as an EP additive.

DOVERLUBE NCL-2 is compatible with naphthenic oil and can be made compatible with paraffinic oil by adding petroleum sulphonate or other couplers.

DOVERLUBE NCL-2 is non-corrosive to both ferrous and non-ferrous surfaces.

DOVERLUBE NCL-2 is extremely effective when used to replace conventional chlorinated additives in low-to heavy-duty metalworking fluids.

Print date: 30-08-25