Supplier - SMART OIL
Smart Base S2215C

0

Universal Emulsifier Package

Typical Properties

Appearance	Amber Liquid
Specific Gravity@25℃	1.000 - 1.100
Viscosity@40°C, cSt	210 - 230
pH Value (5% Water Dilution)	8.0 - 9.5
Std Packaging (NW / GW, Kg)	205.0 / 222.0

Product Description

SMART BASE S2215C is a universal emulsifier package. It not only possesses the elements for soluble oil needs, such as lubricity, EP and antirust, but also has mixed dosage of anti-microbial agents and fungicides; which ensure long usage life. It provides good working conditions and is highly cost-efficient.

SMART BASE S2215C provides superior lubricity and protects non-ferrous metals of copper and aluminium well.

SMART BASE S2215C exhibits strong antirust property, and is suitable for operations on ferrous metals such as cast irons, general steels and alloy steels. End users can use it as water-based rust preventive at 2% dilution ratio after blended to the soluble oils.

Suggested treat rate:

15 - 33% SMART BASE S2215C in SN150 base oil; can blend to different grades of soluble oils.

<u>Applications</u>	Suggested Treat Rates, %wt
	Soft Stell / Alloy Steel / Copper / Aluminum Alloy
Boring & Threading	1:15 / 1:10 / 1:35 / 1:12
Turning, Milling, Drilling	1:25 / 1:20 / 1:35 / 1:15
Sawing	1:25 / 1:25 / 1:35 / 1:15
Grinding	1:40 / 1:40 / 1:40 / 1:40

Print date: 01-07-25