Supplier - SMART OIL
Smart Base CF1104LK

0

Light Color Universal Cutting Oil Package

Typical Properties

Appearance Clear Amber Liquid Viscosity@40°C, cSt 20 - 50 Flash Point C.O.C., °C > 150 Acid Value, mgKOH/g 8.0 - 10.5 Sulfur Content (Active), %wt 10 - 15 (<3.5) Fat Content, %wt > 20 $P_B / P_D, kg^+$ 71 / 315 Std Packaging (NW / GW, Kg) 203.0 / 220.0

Product Description

SMART BASE CF1104LK is a universal neat oil package for the applications of machining, cutting and forming on yellow and ferrous metals. It contains extreme pressure (EP) and anti-wear additives, which can effectively avoid welding at metal contact points between the workpiece cutting tools, so can prolong tool life. Moreover, it contains wetting agent that can effectively elevate the quality of surface finishing of the workpieces.

SMART BASE CF1104LK contains small amount of active sulfur, but suitable for both yellow and ferrous metals as trace amount of corrosion inhibitor has been added to avoid copper corrosion. It does not contain any chlorinated paraffin, and is environmentally friendly.

<u>Applications</u>	<u>Suggested Treat Rates, %wt</u>
Yellow Metals	2 - 3
Ferrous Metals	5 - 10
Stainless Steels	10 - 20

Print date: 01-07-25