

Supplier - DOVER
Maylube S-830
Phosphate Ester
Phosphorus Containing Additives

Typical Properties

Appearance	Clear Amber Fluid
Specific Gravity@60/60°F	1.090
Density, lb/gal	9.08
Viscosity@100°F,SUS(cSt)	1500 (325)
Phosphorus Content,%wt	1.2
pH Value, Neat(5%Concentration)	8.2 (8.0)
Acid Value, meqKOH/g	72
Total Alkalinity, meqKOH/g	7.5

Product Description

MAYLUBE S-830 is a synthetic E.P. and boundary lubricity agent designed to improve performance and finish on both ferrous and non-ferrous alloys . **MAYLUBE S-830** contains no chlorinated or sulfurized materials.

MAYLUBE S-830 is a water soluble compound that produces transparent solutions in all dilutions and can be added directly to most semi-synthetic and synthetic fluid formulations (5 - 15% treat). However, **MAYLUBE S-830** is not compatible with total oil rejecting synthetics.

MAYLUBE S-830 can also be used as a sump side additive for enhanced performance. A recommended treat would be 1 - 2 gallons per 100 gallons coolant sump. **MAYLUBE S-830** can be used in drawing operations that require an oil free, easily removed residual film (20 - 45% treat). Success has been seen in non-ferrous through stainless applications.

MAYLUBE S-830 has replaced highly chlorinated drawing compounds in some of these areas.

MAYLUBE S-830 has a synergistic effect in cutting applications with **MAYLUBE S-003**, at an approximately 1: 1 ratio. Total treat levels recommended would be 5% for light duty machining to 30% for tapping operations.

Applications	Suggested Treat Rates, %wt
Sump Side Booster	1 - 2
Light Duty Cutting Oils	5
Semi-Synthetic	5 - 15
Synthetic	5 - 15
Tapping	20
Drawing	20 - 45

Print date: 04-11-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.