

Supplier - SMART OIL  
**MistQuer W3000**  
*Anti-mist Additive*  
*Other Additives*

### Typical Properties

Appearance	Hazy Milky Emulsion
Specific Gravity@25°C	1.000 - 1.100
Viscosity@100°C, cSt	2000 - 3000
Flash Point C.O.C., °C	≥ 220

### Product Description

**MISTQUER W3000** is a water soluble EO/PO block co-polymer that can lower the surface tension of metal working fluids, so can reduce the mist from fluid splash and foaming.

**MISTQUER W3000** is a low-foaming nonionic surfactant that has good wetting, dispersing characteristics, and also can act as defoamer in water-based systems. Recommended dosage is 3-8% based on different formulation recipes.

Print date: 21-01-26

**Disclaimer:** Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressively requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.