## Supplier - SMART OIL Smart HMPE 9310

High Mwt.Polyester Ester

## **Typical Properties**

Appearance	Clear Amber Liquid
Specific Gravity@25℃	0.900-1.000
Viscosity@40°C, cSt	40 - 60
Acid Value, mgKOH/g	< 8
Flash Point C.O.C.,°C	> 200
Viscosity Index	> 140
Mineral Oil Content	Nil
5%ADDITIVE++95%SN150 PB/PD,kg+	44/100
5%ADDITIVE+5%SMART BASE 2517+90%SN150 PB/PD,kg+	76/315
Std Packaging (NW / GW, Kg)	212.0 / 195.0

## Product Description

**SMART HMPE 9310** is a clear amber, high molecular weight polymeric ester that contains no sulfur, chlorine and phosphorous. Due to its unique molecular structure and high affinity characteristics, it can adhere tightly to the metal surfaces even at elevated temperatures, which performs outstanding anti-frictional and anti-wear properties of lubricants. It can be used in several operations like oil-based formulations, soluble oils and semi-synthetic systems.

**SMART HMPE 9310** has a high degree of satuation that can prevent contamination at contact points of tools and metal surfaces from oxidation.

**SMART HMPE 9310** has high temperature stability and hydrolytic stability, which can extend coolant life even at tough processing.

**SMART HMPE 9310** can replace sulfur, chlorine and phosphorous containing additives with similar performance. Moreover, it can avoid the reduction of product shininess due to the otherwise chemical reaction of the extreme additive with the metals during machining.

**SMART HMPE 9310** possesses high viscosity index and good shear stability; which can maintain the corresponding functions of lubrication, anti-wear and extreme pressure at elevated temperatures at contact points during machining.

**SMART HMPE 9310** is an ash-less additive and has no residue during high temperature operations. It exhibits no corrosion to non-ferrous metals and is suitable for cutting, drawing, and stamping operations on aluminum alloys.

Applications	Suggested Treat Rates, %wt
Threading / Tapping / Cold Head (Cut	3 - 15
Side Only) Drawing Automatic Screw Machines / Stamping	5 - 15 2 - 5

## Print date: 30-08-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressively requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.