Supplier - FUNCTIONAL

V-160

Shear Stable Viscosity Index Improver in Liquid Form Viscosity Modifiers

Typical Properties

Appearance
Density,lbs/gal
Viscosity@100°C,cSt
Shear Stability Index(PSSI), ASTM D6278 30Cycles,%

Viscous Colorless to Light-yellow Liquid
7.10
800 - 1200
22

Product Description

FUNCTIONAL V-160 is a viscosity index improver in concentrated liquid form. It can be used to prepare an economical additive for industrial oils or an aftermarket "oil treatment" additive. It may also be used as an inexpensive thickener for oil, to avoid blending with expensive oils like bright stocks. Customers should evaluate the product in their base oil for compatibility and in particular performance at low temperatures. To improve the low temperature properties of the oil a pour point depressant such as **FUNCTIONAL PD-610** is recommended.

COMPOSITION:

The active ingredient in **FUNCTIONAL V-160** is a copolymer of ethylene and propylene that has been used as a V.I. improver by major oil companies. The diluent in **FUNCTIONAL V-160** is a paraffinic mineral oil.

HANDLING:

Storage at room temperature is recommended. Due to the viscosity of **FUNCTIONAL V-160** at room temperature, elevated temperature (up to approximately 90°C or 200°F) can facilitate handling. **FUNCTIONAL V-160** is a non-hazardous material; see the current Safety Data Sheet.

ApplicationsIndustrial Lubricants and Greases

Suggested Treat Rates, %wt

Print date: 02-12-25