

Supplier - FUNCTIONAL

V-460*Viscosity Modifiers**Food Grade Superior High Shear Stable Viscosity Index Improver*Typical Properties

Specific Gravity	0.860
Density,lbs/gal	7.16
Flash Point,°C(°F)	150 (302)
Color (ASTM D1500)	Clear to Slight Turbid
Thickening Efficiency@100°C(10.0% in ISO22 Oil),cSt	7.0 - 12.0
Percent Viscosity Loss(ASTM D6278) 30cycles,%wt	7.5
Percent Shear Stability Index(PSSI)ASTM D6278,%wt 25	25
Std Packaging (NW / GW, Kg)	217.0 / 200.0

Product Description

FUNCTIONAL V-460 is a viscosity index (VI) improver that may be used in preparing industrial fluids and lubricants. It may also be used without dilution as a supplemental crankcase additive for the automotive aftermarket.

COMPOSITION:

The active thickener in **FUNCTIONAL V-460** is a copolymer of ethylene and propylene that has been used as a V.I. improver by major oil companies. The diluent in **FUNCTIONAL V-460** is white oil. Both ingredients are nonhazardous, and are listed as suitable for use in lubricants with incidental food contact (21 CFR 178.3570).

HANDLING:

Due to the viscosity of **FUNCTIONAL V-460**, elevated temperature (up to approximately 90°C (200°F) can facilitate handling. Safe handling precautions are the same as those to be taken with the base oil; see the current Material Safety Data Sheet.

Applications

Industrial Lubricants and Greases

Suggested Treat Rates, %wt

5 - 20

Print date: 27-09-24

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.