Supplier - FUNCTIONAL PD-600

### Cold-flow Improver for Mineral Oil-based Lubricants

# **Typical Properties**

| Appearance                    | Light-colored Liquid |
|-------------------------------|----------------------|
| Odor                          | Mild Fatty           |
| Specific Gravity              | 0.880                |
| Density,lbs/gal               | 7.33                 |
| Flash Point,°C(°F)            | ≥ 135 (275)          |
| Kinematic Viscosity@100°C,cSt | 70                   |
| Std Packaging (NW / GW, Kg)   | 217.0 / 200.0        |

# **Product Description**

**FUNCTIONAL PD-600** is a wax-crystal modifier. Its primary use is in improving the cold-flow properties of mineral oil-based lubricants at temperatures below their cloud points. It is effective under both rapid cooling and extended cold storage conditions.

**FUNCTIONAL PD-600** is effective in hydraulic fluids, chain saw oils, pneumatic-tool lubricants and other lubricants made from solvent extracted neutral base stocks as well as hydro-cracked base stocks.

## **Composition:**

The active additive in **FUNCTIONAL PD-600** is a proprietary polymer. The diluent oil in **FUNCTIONAL PD-600** is light paraffinic oil.

#### **Handling:**

Any convenient technique may be used for blending. Safe handling precautions are the same as those to be taken with vegetable oils; see the current Material Safety Data Sheet.

| <u>Applications</u>                    | Suggested Treat Rates, %wt |
|--|----------------------------|
| Reduce Pour Point of Mineral Oils (□   | 0.1                        |
| 40°F)                                  |                            |
| Stability in Extended Storage (☐ 40°F) | 0.2                        |

Print date: 14-09-25