

Supplier - SMART OIL

Smart Base CP60

0

Extreme Pressure Additive

Typical Properties

Appearance	Viscous Liquid
Specific Gravity@25°C	1.300 - 1.400
Viscosity@40°C, cSt	10000 - 12000
Flash Point C.O.C., °C	≥ 220
Chlorine content, %	55 - 62
Std Packaging (NW / GW, Kg)	250.0 / 267.0

Product Description

SMART BASE CP60 is a chlorinated paraffin with high viscosity, low volatile, low odor, non-corrosive and higher chlorine content.

SMART BASE CP60 has good lubricity and extreme pressure characteristics, suitable for use in stamping, drawing and cutting operations.

SMART BASE CP60 is suitable for use in oil-based formulations.

Print date: 01-07-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.